

# Safety data sheet

Issue date: 17-04-2013  
Version: 01.00/GBR

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name: PREVAL SPRAY GUN POWER UNIT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Propellants.

### 1.3. Details of the supplier of the safety data sheet

Supplier: Chicago Aerosols - Bridgeview Facility  
8407 South 77<sup>th</sup> Avenue  
60455 Bridgeview, IL 60455  
USA  
Tel: +001 708 598 7100

### 1.4. Emergency telephone number

0870 600 6266 (UK only) Only available to health professionals.

---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

DPD-classification: F+a;R12A

CLP-classification: Flam. Aerosol 1;H222a

*Please see section 16 for the full text of R-phrases and H-phrases.*

Most serious harmful effects: Extremely flammable.  
The product releases vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

### 2.2. Label elements



Signal word: Danger

H-phrases: Extremely flammable.

P-phrases: Avoid breathing dust/fume/gas/mist/vapours/spray.  
Use only outdoors or in a well-ventilated area.

Supplemental information: Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Keep out of reach of children.

### 2.3. Other hazards

The product does not contain any PBT or vPvB substances.

---

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Registration number	CAS/EC Number	Substance	DSD-classification/ CLP-classification	w/w%	Note
.	115-10-6	Dimethyl ether	Fx;R12	20-50	13
.	204-065-8	.	Flam. Gas 1;H220 Press. Gas;H280	.	.
.	75-28-5	Isobutane (containing < 0.1 %	Fx;R12	20-50	.
.	200-857-2	butadiene (203-450-8))	Flam. Gas 1;H220 Press. Gas;H280	.	.
.	74-98-6	Propane	Fx;R12	20-50	.
.	200-827-9	.	Flam. Gas 1;H220 Press. Gas liq. gas;H280	.	.

13) The substance has a national exposure limit.

Please see section 16 for the full text of R-phrases and H-phrases.

---

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation:	Seek fresh air. Seek medical advice in case of persistent discomfort.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.
Skin:	Remove contaminated clothing. Wash skin with soap and water. Seek medical advice in case of persistent discomfort.
Eyes:	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
Burns:	Flush with water until pain ceases. Remove clothing that is not stuck to the skin – seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.
Other information:	When obtaining medical advice, show the safety data sheet or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation of spray mist may cause irritation to the upper airways. The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.
Unsuitable extinguishing media	Do not use water stream, as it may spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Heating will cause a rise in pressure in packaging with a risk of bursting. CAUTION! Aerosol containers may explode. Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

#### 5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Stay upwind/keep distance from source. Provide adequate ventilation. Smoking and naked flames prohibited.
For emergency responders:	In addition to the above: Normal protective clothing equivalent to EN 469 is recommended.

## 6.2. Environmental precautions

Avoid unnecessary release to the environment.

## 6.3. Methods and material for containment and cleaning up

Wipe up drops and splashes with a cloth.

## 6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work. Smoking and naked flames prohibited.

### 7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50 °C.

### 7.3. Specific end use(s)

None.

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Occupational exposure limits:

Ingredient:	Exposure limit	Remarks
Dimethyl ether	400 (8h), 500 (15m) ppm 766 (8h), 958 (15m) mg/m <sup>3</sup>	-

Legal basis: EH40/2005 Workplace exposure limits. Last amended December 2011.

Measuring methods: Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

### 8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles if there is a risk of eye splash. Eye protection must conform to EN 166.

Personal protective equipment, skin protection: Plastic or rubber gloves recommended.

Personal protective equipment, respiratory protection: In case of insufficient ventilation, wear respiratory protective equipment. Filter type: AX. Respiratory protection must conform to one of the following standards: EN 136/140/145.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Aerosol  
Colour: Clear  
Odour: Weak Solvent  
Odour threshold: No data  
pH (solution for use): No data  
pH (concentrate): No data  
Melting point/freezing point: No data  
Initial boiling point and boiling range: Min. -42.2 °C  
Max. -11.7 °C  
Flash point: -104.4 °C

Evaporation rate:	> 1 (ethyl ether = 1)
Flammability (solid, gas):	No data
Upper/lower flammability limits:	No data
Upper/lower explosive limits:	1.8 vol% - 18 vol%
Vapour pressure:	524 kPa gauge @ 21.1 °C
Vapour density:	1.8
Relative density:	0.6
Solubility:	No data
Partition coefficient	No data
n-octanol/water:	
Auto-ignition temperature:	No data
Decomposition temperature:	No data
Viscosity:	No data
Explosive properties:	No data
Oxidising properties:	No data

## 9.2. Other information

None.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with the following: Strong oxidisers/ Acids/ Metals.

### 10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

### 10.3. Possibility of hazardous reactions

Product vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 10.4. Conditions to avoid

Avoid heating and contact with ignition sources. Avoid direct sunlight. Avoid temperatures >50 °C.

### 10.5. Incompatible materials

Strong oxidisers/ Acids/ Metals.

### 10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity - oral:	Spray mist in mouth may irritate mucous membranes in mouth and throat. The product does not have to be classified. Test data are not available.
Acute toxicity - dermal:	The product does not have to be classified. Test data are not available.
Acute toxicity - inhalation:	The product does not have to be classified. Test data are not available.
Skin corrosion/irritation:	May cause slight irritation. The product does not have to be classified. Test data are not available.
Serious eye damage/eye irritation:	Temporary irritation. The product does not have to be classified. Test data are not available.
Respiratory sensitisation or skin sensitisation:	The product does not have to be classified. Test data are not available.
Germ cell mutagenicity:	The product does not have to be classified. Test data are not available.
Carcinogenic properties:	The product does not have to be classified. Test data are not available.
Reproductive toxicity:	The product does not have to be classified. Test data are not available.
	Inhalation of spray mist may cause irritation to the upper airways. The product releases organic

Single STOT exposure: solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. The product does not have to be classified. Test data are not available.

Repeated STOT exposure: The product does not have to be classified. Test data are not available.

Aspiration hazard: The product does not have to be classified. Test data are not available.

Other toxicological effects: None known.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

The product does not have to be classified. Test data are not available for all substances

### 12.2. Persistence and degradability

Potentially degradable. Test data are not available.

### 12.3. Bioaccumulative potential

No bioaccumulation expected. Test data are not available.

### 12.4. Mobility in soil

Test data are not available.

### 12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

### 12.6. Other adverse effects

None known.

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Avoid unnecessary release to the environment.

Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility with the specifications set out below.

Aerosol sprays: EWC code: 16 05 04 Gases in pressure containers containing dangerous substances. Wiping cloths with organic solvents: EWC code: 15 02 02 Absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

Absorbent/cloth contaminated with the product:  
EWC code: 15 02 02 absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

---

## SECTION 14: Transport information

### ADR/RID

14.1. UN number 1950

14.2. UN proper shipping name AEROSOLS

14.3. Transport hazard class(es) 2.1

14.4. Packing group -

Hazard identification number -

Tunnel restriction code: D

14.5. Environmental hazards            The product should not be labelled as an environmental hazard (symbol: fish and tree).

**ADN**

14.1. UN number                        1950  
14.2. UN proper shipping name        AEROSOLS  
14.3. Transport hazard class(es)      2.1  
14.4. Packing group                    -  
14.5. Environmental hazards            The product should not be labelled as an environmental hazard (symbol: fish and tree).  
Environmental hazard in tank vessels:                    -

**IMDG**

14.1. UN number                        1950  
14.2. UN proper shipping name        AEROSOLS  
14.3. Transport hazard class(es)      2.1  
14.4. Packing group                    -  
14.5. Environmental hazards            The product is not a Marine Pollutant (MP).  
IMDG Code segregation group:        -

**ICAO/IATA**

14.1. UN number                        1950  
14.2. UN proper shipping name        AEROSOLS, FLAMMABLE  
14.3. Transport hazard class(es)      2.1  
14.4. Packing group                    -

**14.6. Special precautions for user**

None.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

---

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Special provisions:                      Directive 2012/18/EU (Seveso), P3a FLAMMABLE AEROSOLS: Column 2: 150 (net) t, Column 3: 500 (net) t.  
Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.

**15.2. Chemical safety assessment**

Chemical safety assessment has not been performed.

---

**SECTION 16: Other information**

Abbreviation explanations:            PBT: Persistent, Bioaccumulative and Toxic  
vPvB: Very Persistent and Very Bioaccumulative  
STOT: Specific Target Organ Toxicity

Classification method:                Calculation based on the hazards of the known components.

R-phrases:                                R12 Extremely flammable.

H-phrases: R12A Extremely flammable.  
H220 Extremely flammable gas.  
H222a Extremely flammable.  
H280 Contains gas under pressure, may explode if heated.

Training: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Other information: This safety data sheet is in accordance with 1907/2006/EC (REACH) and subsequent amendments.

---

AOA/ Bureau Veritas HSE Denmark A/S Birkemosevej 7, DK-6000 Kolding T: +45 75508811, F: +45 75508810, E-mail: infohse@dk.bureauveritas.com, Web: www.hse.bureauveritas.dk (Made in Toxido®) UK